

**SAFETY DATA SHEET****CARBON DIOXIDE****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product name	Carbon dioxide
Trade name	Carbon dioxide – Carbon dioxide Food Grade – R744
Additional identification	
Chemical name	Carbon dioxide
Chemical formula	CO <sub>2</sub>
INDEX No.	-
CAS-No.	124-38-9
EC No.	204-696-9
REACH Registration No.	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses	Industrial and professional. Perform risk assessment prior to use. Aerosol propellant. Balance gas for mixtures. Beverage applications. Biocidal uses. Blanketing gas. Blast cleaning. Calibration gas. Carrier gas. Chemical synthesis. Combustion, melting and cutting processes. Cooling applications. Fire suppressant gas. Food freezing. Food packaging gas. Freezing, Cooling and heat transfer. Inerting gas. Inflation systems. Laboratory use. Laser gas. Plant growth promoter. Pressure head gas, operational assist gas in pressure systems. Process gas. Purge gas. Refrigerant. Solvent for extraction. Special effects (entertainment). Test gas. Consumer use. Propellant gas. Shielding gas in gas welding.
Uses advised against	Industrial or technical grade unsuitable for medical and/or food applications or inhalation.

**1.3 Details of the supplier of the safety data sheet**

Supplier	Gastec-Vesta srl Via Tasso, 29 - 20010 Pogliano Milanese (Mi) Tel +39.02.93282361 info@gastecvesta.com
E-mail	

**1.4. Emergency telephone number**

Emergency telephone number	Tel.: 118 / +39.02.932821
----------------------------	---------------------------

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or 1999/45/EC as amended  
Not classified

Classification according to Regulation (EC) No 1272/2008 as amended.  
Physical Hazards

## SAFETY DATA SHEET

# CARBON DIOXIDE

Gases under pressure

Compressed gas

H280: Contains gas under pressure; may explode if heated.

### 2.2 Label Elements



Signal Words

Warning

Hazard Statement(s)

H280: Contains gas under pressure; may explode if heated.

Precautionary Statement

Prevention

None

Response

None

Storage

P403: Store in a well-ventilated place.

Disposal

None

Supplemental label information

EIGA-As: Asphyxiant in high concentrations.

### 2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Chemical name

Carbon dioxide

INDEX No.

--

CAS-No.

124-38-9

EC No.

204-696-9

REACH Registration No.

Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration

Purity

100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted

Carbon dioxide – Carbon dioxide Food Grade – R744

Trade name

## SECTION 4: First Aid Measures

General

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

### 4.1 Description of first aid measures

Inhalation

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if

**SAFETY DATA SHEET****CARBON DIOXIDE**

Eye contact	breathing stopped. Low concentrations of CO <sub>2</sub> cause increased respiration and headache Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
Skin Contact Ingestion	Contact with evaporating liquid may cause frostbite or freezing of skin. Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed**

Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

**4.3 Indication of any immediate medical attention and special treatment needed**

Hazards	Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.
Treatment	Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**SECTION 5: Firefighting Measures**

General Fire Hazards	Heat may cause the containers to explode.
----------------------	---

**5.1 Extinguishing media**

Suitable extinguishing media	Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.
Unsuitable extinguishing media	None

**5.2 Special hazards arising from the substance or mixture**

Hazardous Combustion Products	None
	None

**5.3 Advice for firefighters**

Special firefighting procedures	In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.
Special protective equipment for firefighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for firefighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**SAFETY DATA SHEET****CARBON DIOXIDE****SECTION 6: Accidental Release Measures****6.1 Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Guideline EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask Requirements, testing, marking.

**6.2 Environmental Precautions**

Prevent further leakage or spillage if safe to do so.

**6.3 Methods and material for containment and cleaning up**

Provide adequate ventilation.

**6.4 Reference to other sections**

Refer to sections 8 and 13.

**SECTION 7: Handling and Storage****7.1 Precautions for safe handling**

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to

**SAFETY DATA SHEET****CARBON DIOXIDE**

another. Container valve guards or caps should be in place. Depressurisation of liquid CO<sub>2</sub> below approximately 5 bar can create solid CO<sub>2</sub> which may block protective devices, pipework and create dry-ice within containers. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide.

**7.2 Conditions for safe storage, including any incompatibilities**

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage.

Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

**7.3 Specific end use(s):**

None

**SECTION 8: Exposure Controls/Personal Protection****8.1 Control Parameters**

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values		Source
Carbon dioxide	TWA	5,000 ppm	9,150 mg/m <sup>3</sup>	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
	STEL	15,000 ppm	27,400 mg/m <sup>3</sup>	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
	TWA	5,000 ppm	9,150 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directive 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)

**8.2 Exposure controls**

Appropriate engineering controls

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (e.g. welded pipes). Do not eat, drink or smoke when using the product.

**Individual protection measures, such as personal protective equipment**

General information

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered.

Keep self contained breathing apparatus readily available for emergency use.

## SAFETY DATA SHEET

# CARBON DIOXIDE

Eye/face protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection
Skin protection	
Hand Protection	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks.
Body protection	No special precautions.
Other	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection	Not required.
Thermal hazards	No precautionary measures are necessary.
Hygiene measures	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls	For waste disposal, see section 13.

## SECTION 9: Physical And Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	Gas
Form	Liquefied gas
Colour	Colorless
Odour	Odorless
Odour Threshold	Odour threshold is subjective and is inadequate to warn of over exposure.
pH	3.2 - 3.7 The pH of saturated CO <sub>2</sub> solutions varies from 3.7 at 101 kPa (1 atm) to 3.2 at 2370 kPa (23.4 atm).
Melting Point	- 56.6°C
Boiling Point	- 78.5°C
Sublimation Point	- 78.5°C.
Critical Temp. (°C)	31.0 °C
Flash Point	Not applicable to gases and gas mixtures.
Evaporation Rate	Not applicable to gases and gas mixtures.
Flammability (solid, gas)	Non flammable gas
Flammability limit - upper (%)	not applicable.
Flammability limit - lower (%)	not applicable.
Vapour pressure	45.1 bar (10 °C).
Vapour density (air=1)	1.522 (21° C)
Relative density	1.512
Solubility (ies)	
Solubility in Water	23900 mg/l (25° C)
Partition coefficient (n-octanol/water)	0.83
Autoignition Temperature	not applicable.
Decomposition Temperature	Not known

## SAFETY DATA SHEET

# CARBON DIOXIDE

Viscosity  
Kinematic viscosity  
Dynamic viscosity  
Explosive properties  
Oxidising Properties

No data available.  
0.07 mPa.s (20 °C)  
Not applicable.  
not applicable.

## 9.2 Other information

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Molecular weight  
44.01 g/mol (CO<sub>2</sub>)

## SECTION 10: Stability and Reactivity

### 10.1 Reactivity

No reactivity hazard other than the effects described in sub-section below.

### 10.2 Chemical Stability

Stable under normal conditions.

### 10.3 Possibility of Hazardous Reactions

None.

### 10.4 Conditions to Avoid

None.

### 10.5 Incompatible Materials

No reaction with any common materials in dry or wet conditions.

### 10.6 Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological Information

General information

In high concentrations may cause rapid circulatory deterioration even at normal levels of oxygen concentration. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness and even death..

### 11.1 Information on toxicological effects

Acute toxicity – Oral Product  
Acute toxicity – Dermal Product  
Acute toxicity – Inhalation Product  
Skin Corrosion/Irritation Product  
Serious Eye Damage/Eye Irritation Product  
Respiratory or Skin Sensitisation Product

Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.

**SAFETY DATA SHEET****CARBON DIOXIDE**

Germ Cell Mutagenicity Product  
Carcinogenicity Product  
Reproductive toxicity Product  
Specific Target Organ Toxicity - Single Exposure Product  
Specific Target Organ Toxicity - Repeated Exposure Product  
Aspiration Hazard Product

Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Based on available data, the classification criteria are not met.  
Not applicable to gases and gas mixtures.

**SECTION 12: Ecological Information****12.1 Toxicity**

Acute toxicity Product

No ecological damage caused by this product.

**12.2 Persistence and Degradability Product**

The substance is naturally occurring.

**12.3 Bioaccumulative Potential Product**

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in Soil Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5 Results of PBT and vPvB assessment Product**

Not classified as PBT or vPvB.

**12.6 Other Adverse Effects**

Global Warming Potential

Global warming potential: 1 When discharged in large quantities may contribute to the greenhouse effect.

Carbon dioxide

UN / IPCC. Greenhouse Gas Global Warming Potentials (IPCC Fourth Assessment Report, Climate Change, Table TS.2 - Global warming potential: 1 100-yr

**SECTION 13: Disposal Considerations****13.1 Waste treatment methods**

General information

Do not discharge into any place where its accumulation could be dangerous. Vent to atmosphere in a well-ventilated place.

Disposal methods

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods.

European Waste Codes

Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

Container

16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

## SAFETY DATA SHEET

# CARBON DIOXIDE

### SECTION 14: Transport Information

#### ADR

14.1 UN Number	UN 1013
14.2 UN Proper Shipping Name	CARBON DIOXIDE
14.3 Transport Hazard Class (es)	
Class	2
Label(s)	2.2
Hazard No. (ADR)	20
Tunnel restriction code	(C/E)
Emergency Action Code	2T
14.4 Packing Group	-
14.5 Environmental hazards	not applicable
14.6 Special precautions for user	-

#### RID

14.1 UN Number	UN 1013
14.2 UN Proper Shipping Name	CARBON DIOXIDE
14.3 Transport Hazard Class (es)	
Class	2
Label(s)	2.2
14.4 Packing Group	-
14.5 Environmental hazards	not applicable
14.6 Special precautions for user	-

#### IMDG

14.1 UN Number	UN 1013
14.2 UN Proper Shipping Name	CARBON DIOXIDE
14.3 Transport Hazard Class (es)	
Class	2.2
Label(s)	2.2
EmS No.	F-C, S-V
14.3 Packing Group	-
14.5 Environmental hazards	not applicable
14.6 Special precautions for user	-

#### IATA

14.1 UN Number	UN 1013
14.2 Proper Shipping Name	CARBON DIOXIDE
14.3 Transport Hazard Class (es)	
Class	2.2
Label(s)	2.2
14.4 Packing Group	-
14.5 Environmental hazards	not applicable
14.6 Special precautions for user	-
Other information	
Passenger and cargo aircraft	Allowed
Cargo aircraft only	Allowed

**SAFETY DATA SHEET****CARBON DIOXIDE****14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

not applicable

**Additional identification**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulations**

Directive 96/61/EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Carbon dioxide	124-38-9	100 %

**National Regulations**

Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010.

**15.2 Chemical safety assessment:**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other Information****Revision Information**

Not relevant.

**Key literature references and sources for data**

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to: Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>). European Chemical Agency: Guidance on the Compilation of Safety Data Sheets. European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search> European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling

## SAFETY DATA SHEET

## CARBON DIOXIDE

guide. International Programme on Chemical Safety (<http://www.inchem.org/>) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets. Matheson Gas Data Book, 7th Edition. National Institute for Standards and Technology (NIST) Standard Reference Database Number 69. The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>). The European Chemical Industry Council (CEFIC) ERICards. United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>) Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH). Substance specific information from suppliers. Details given in this document are believed to be correct at the time of publication. EH40 (as amended) Workplace exposure limits. <http://apps.echa.europa.eu/registered/registered -sub.aspx#search> European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide. International Programme on Chemical Safety (<http://www.inchem.org/>) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets. Matheson Gas Data Book, 7th Edition. National Institute for Standards and Technology (NIST) Standard Reference Database Number 69. The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>). The European Chemical Industry Council (CEFIC) ERICards. United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>) Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH). Substance specific information from suppliers. Details given in this document are believed to be correct at the time of publication. EH40 (as amended) Workplace exposure limits.

## Wording of the R-phrases and H-statements in sections 2 and 3

H280 - Contains gas under pressure; may explode if heated.

## Training information

Users of breathing apparatus must be trained. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Ensure operators understand the hazards.

## Classification according to Regulation (EC) No 1272/2008 as amended

Press. Gas Liq. Gas, H280

## Other information

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation.

**SAFETY DATA SHEET****CARBON DIOXIDE**

Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Note: When the Product Name appears in the SDS header the decimal sign and its position comply with rules for the structure and drafting of international standards, and is a comma on the line. As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

Last revised date

04.04.2018

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

End of document